

Miller® Anchor Grips™

Product description

The Miller Anchor Grip is a portable and reusable anchorage connector designed for use in concrete applications. A variety of connecting devices including a shock-absorbing lanyard or self-retracting lifeline can be attached to the Anchor Grip.

FEATURES

- A safe anchor point is established when the Miller® Grip™ anchor is inserted into a properly-sized, cured concrete hole.
- The reusable Miller Grip anchor can be removed and simply re-installed in a new location.
- Designed for vertical or overhead/ceiling surface applications.
- Constructed from stainless steel, aluminium and other non-corrosive materials for a longer service life.
- Designed for use in cured concrete with a compression strength of at least 3,000 psi as a single-user fall protection application.

APPLICATIONS

- General Construction
- Concrete applications

496



497



Technical Information

	496	497
Tensile Strength:	22kN	44kN
Hole size:	19mm (3/4")	25.4mm (1")

Standards

Refer to AS/NZS 1891.4 for information on anchorage selection and strength.

Ordering Details

PART NO.	DESCRIPTION	OPERATION	MIN QTY	CAT	PACKAGE DIMENSIONS	BARCODE
496	Anchor grip	Single user	1	A	290 x 60 x 60	9333633006899
497	Anchor grip	Single user or dual user with temp static line	1	A	380 x 60 x 60	9333633006905

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166
New Zealand 0800 322 200
www.honeywellsafety.com