

BANDIDO

A MODEL FOR GENUINE PROTECTION

Made entirely of highly-resistant polycarbonate, BANDIDO is the perfect value option.



1667201 • Clear Lens



1667202 • Smoke Lens



1667203 • Amber Lens






28 g

- + ALL POLYCARBONATE FRAME WRAP-AROUND FIT**
- + AMBER LENS AVAILABLE FOR BETTER CONTRAST AND PERCEPTION IN LOW LIGHT CONDITIONS**
- + ALS ANTI-FOG / ANTI-SCRATCH COATING**
- + SINGLE PIECE, OPTICALLY CORRECT, 10 BASE LENS**

bollé
SAFETY

BANDIDO

A MODEL FOR GENUINE PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BANDIDO	 Clear	1667201	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1667202	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Amber	1667203	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear and amber lenses.

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear & amber).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Drilling
- Laboratory and dental
- Driving
- Solar UV exposure

MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- Medical and dental
- Food Industry

LENSES

- 2mm polycarbonate
- 10 base curve
- 'ALS' Anti-fog/anti-scratch coating on both sides of lens: Clear, Smoke and Amber
- 99.9% UV 385 - Clear
- 99.9% UV 400 - Amber and Smoke

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 10
FRAME	PC
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

14/12/2018

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY