AS DUO

UNBEATABLE DESIGN





1669211 • Orange Frame with SBR Foam / Clear Duo Lens / No vents / No Notch / Fully Foam Seal



1650708 • Charcoal Frame with SBR Foam / Clear Duo Lens / Clear Mouth Guard / No vents / No Notch / Fully Foam Seal

- 1650601 DUO CLEAR LENS
- 1650602 DUO SMOKE LENS
- 1650015 RX ADAPTOR
- 1669204 MOUTH GUARD
- 1650014 LENS TEAR OFF (1 PACK = 10 SETS / 4 PER SET)

122 g

- + ADJUSTABLE STRAP
- **+** FITS OVER PRESCRIPTION GLASSES
- + COMPATIBLE WITH HALF-MASK RESPIRATOR
- OPTIONAL PRESCRIPTION RX **ADAPTOR AVAILABLE**

- **+** THE ULTIMATE IN ANTI-FOG PROTECTION **+** SPLASH, GAS AND DUST APPROVED
 - PVC FRAME WITH CLOSED SBR FOAM FOR ADDED COMFORT AND PROTECTION



BLAST DUO

UNBEATABLE DESIGN

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BLAST DUO CLEAR	Orange Frame with SBR Foam / Clear Duo Lens / No vents / No Notch / Fully Foam Seal	1669211	CIOD	AS/NZS 1337.2010	Anti-scratch/Anti-fog
	Charcoal Frame with SBR Foam / Clear Duo Lens / Clear Mouth Guard / No vents / No Notch / Fully Foam Seal	1650708	CIOD	AS/NZS 1337.2010	Anti-scratch/Anti-fog

LENS MARKING

- C. The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.
- **D.** The letter 'D' signifies appropriate for protection against dust.

OCULAR LENS CATEGORY:

O. Range of luminous transmittance 80-100% (clear).

LENSES

- 'ALS' anti-fog / anti-scratch coating on both sides of Clear and Smoke lens
- 99.9% UV 385 Clear

FRAME MARKING

AS/NZS 1337.1.2010: Tested and approved to. AS/NZS 1337.1.2010 -Medium Impact protection. Meets the requirement of splash approval when used with the supplied head strap correctly adjusted.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS			
LENSES	PC - 2,2 mm - Curve 9		
FRAME	PC + PVC		
STRAP	Non Applicable		
FOAM	SBR		
SPARE LENSES	No		

13/08/2019



NEW ZEALAND: T.: 0800 2655 369 E: sales@bollesafety.com.au

