COVERALL

FUNCTIONAL AND EFFECTIVE

Functional and versatile PVC goggles that fit over prescription glasses. Available in ventilated and sealed versions.











Clear with indirect vents top/bottom: 1686101



Smoke with indirect vents top/bottom: 1686102



Platinum Clear Vents Fully Sealed: 1687101



Platinum Smoke Vents Fully Sealed: 1687102

- **+** ECONOMIC MODEL
- + ADJUSTABLE NYLON STRAP
- + FITS OVER PRESCRIPTION GLASSES
- + 2 VERSIONS: VENTILATED OR SEALED
- + �PLATINUM' (*P) COATING



COVERALL

FUNCTIONAL AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
COVERALL	Clear Indirect Vented	1686101	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Smoke Indirect Vented	1686102	CI3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Platinum Clear Vents Fully Sealed	1687101	CIO & + P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (+)
	Platinum Smoke Vents Fully Sealed	1687102	Cl3 & ⁺ ₽	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (⁺ P)

LENS MARKING

- P. Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- C. The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- O. Range of luminous transmittance 80-100% (Clear).
- 3. Range of luminous transmittance 8-18% (Smoke).

LENSES

- •Anti-fog / anti-scratch coating on both sides of Clear and Smoke Ventilated model lens
- Platinum coating on sealed version Clear and Smoke Lens
- 99.9% UV 385 Clear
- 99.9% UV 400 Smoke

FRAME MARKING

AS/NZS 1337.1:2010: Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm ball at 45 m/s. Meets the requirements of splash approval when used with the supplied head strap correctly adjusted.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

TECHNOLOGIES



The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

CHARACTERISTICS			
LENSES	PC - 2,2 mm - Curve 4		
FRAME	PVC		
TEMPLES	Non applicable		
STRAP	Nylon		
FOAM	No		
SPARE LENSES	No		











Non-contractual pictures

01/06/2020

Bollé Safety AU Pty Limited 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: sales@bollesafety.com.au

Hong Kong Bollé Safety 818, 8/F, Ocean Centre, Harbour City, 5 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong T.: +852 2732 5038

