

HS 66-398

BLACK SMELTER BOOT



by Honeywell

STYLE SPECIFICATIONS



DESCRIPTION:

Heat resistant and flame retardant leather smelter boot

Colour: Black

Sizes: 5 - 14, 6½ - 10½

Standards:

AS/NZS 2210.3:2009

EN ISO 20345:2011, ASTM F2413-11

Application: Steel & Smelter

FEATURES:

- Heat resistant and flame retardant leather upper.
- Uppers designed to assist the run-off of molten metal.
- TECTuff® toe bumper to protect against scuffing.
- Leather lining along the heel and the foot area of the boot to provide additional heat protection
- PORON XRD™ flexible, lightweight internal metatarsal guard.
- COMFORTcushion® Impact Absorption System with PORON™ protects the heel and ball of the foot.
- NATUREform® steel toe cap with a wide profile for greater comfort.
- Full breathable lining with a padded comfort collar.
- NANOLite® footbed with a gently raised surface to help reduce fatigue
- Excellent slip resistant sole; SRC slip resistant classification.
- Electrical Hazard (EH) Protection.
- Heavy Duty Nitrile Rubber dual density sole, with an in-fill comfort layer of urethane cushioning, coupled with a high density hard-wearing nitrile rubber outsole.
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact
Absorption



NATUREform
wide profile Type
1 safety toe cap



Water Resistant
Leather



Steel Safety
Toe Cap



Metatarsal
protection



NANOLite
footbed

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Electrical Hazard
Resistant

OLIVER FOOTWEAR



Facebook.com/oliversafetyfootwear



@oliverfootwear

Honeywell