

TENCATE TECASAFE® PLUS 700 TAPED FR RIPSTOP PANT

BP8490T



Navy
(BPCT)



Features

- Inherent Flame resistant fabric - Tecasafe® Plus Ripstop
- Sto-nor 9801 FR Reflective taped around upper legs
- Straight waistband
- Front angled pockets with reinforced opening
- YKK branded zip front fly
- Single back patch pocket with plastic press stud flap closure
- Wide belt loops

Fabric

- TenCate Tecasafe® Plus 700AI Ripstop FR Aramid// Lyocell/ Modacrylic 238gsm

Arc Thermal Protection Value

- ATPV 8.4

Personal Protective Equipment Category

- PPE 2

Size

- Reg: 77R-112R
- Stout: 87S-132S



TENCATE Tecasafe® Plus

BP8490T

www.bisleyworkwear.com.au

TECHNICAL FAQ's

What is the inleg length on Regular (crotch to finish hem)?

- **77:** 80cm, **82:** 82cm, **87:** 82cm, **92:** 84cm, **97:** 84cm, **102:** 86cm, **107:** 86cm, **112:** 88cm

What is the inleg length on Stout (crotch to finish hem)?

- **87:** 78cm, **92:** 80cm, **97:** 80cm, **102:** 82cm, **107:** 82cm, **112:** 84cm, **117:** 84cm, **122:** 84cm, **127:** 84cm, **132:** 84cm

SIMILAR PRODUCTS



BP8090T
TENCATE TECASAFE®
PLUS 700 TAPED
FR PANT



BP8190T
TENCATE TECASAFE®
PLUS 580 TAPED
FR PANT



BPC8092T
TENCATE TECASAFE® PLUS
700 TAPED ENGINEERED FR
VENTED CARGO PANT

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling

Australian/ New Zealand Standards

AS/NZS 4399:2017: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ for all colours*

AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *Retro-reflective tape used on this garment meets the specific retro-reflective performance requirements under this standard for Class R material.*

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 8.4 cal/cm² PPE 2
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten or flaming debris. No after flame.

PANTS: Regular

MENS

To fit waist size (cm)	77	82	87	92	97	102	107	112
To fit waist size (inches)	30	32	34	36	38	40	42	44
Inner leg length (cm)	80	82	82	84	84	86	86	88

PANTS: Stout

MENS

To fit waist size (cm)	87	92	97	102	107	112	117	122	127	132
To fit waist size (inches)	34	36	38	40	42	44	46	48	50	52
Inner leg length (cm)	78	80	80	82	82	84	84	84	84	84

BP8490T

www.bisleyworkwear.com.au