

WOMENS TECASAFE® PLUS 700 TAPED FR CARGO PANT

BPL8092T

Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective tape around leg at the knee section
- Curve shape waistband to prevent gaping at back
- YKK branded zip front fly
- Front angled pocket with reinforce opening
- RHS back welt pocket with touch tape closure
- RHS mobile phone welt pocket
- LHS bellow cargo pocket with plastic stud flap closure

Fabric

- TenCate Tecasafe® Plus 700A
FR Modacrylic/Lyocell/Aramid
238gsm

Arc Thermal Protection Value

- ATPV 11

Personal Protective Equipment Category

- PPE 2

Size

- 6 - 24



Navy
(BPCT)



TENCATE
Tecasafe® Plus

BPL8092T

www.bisleyworkwear.com.au

TECHNICAL FAQ'S

What is the inleg length (crotch to finish hem)?

- **6:** 78cm, **8:** 80cm, **10:** 80cm, **12:** 82cm, **14:** 82cm, **16:** 84cm, **18:** 84cm, **20:** 86cm
- **22:** 86cm, **24:** 86cm

SIMILAR PRODUCTS



BL8082T
TENCATE TECASAFE® PLUS 700
WOMENS TAPED 2TONE HI VIS
FR VENTED SHIRT LS



BP8090T
TENCATE TECASAFE®
PLUS 700 TAPED
FR PANT



BP8190T
TENCATE TECASAFE®
PLUS 580 TAPED
LW FR PANT

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998** Textiles - Care Labelling
- **AS/NZS 2622:1996** Textile Products - Fibre Content Labelling

Australian/ New Zealand Standards

AS/NZS 4399:2017 SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ for all colours*

AS/NZS 1906.4:2010 HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *Retro-reflective tape used on this garment meets the specific retro-reflective performance requirements under this standard for Class R material.*

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 10.0 cal/cm² PPE 2
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten or flaming debris. No after flame.

ALL STYLES

WOMENS

Size	6	8	10	12	14	16	18	20	22	24
To fit bust size (cm)	80	85	90	95	100	105	110	115	120	125
To fit natural waist size (cm)	60	65	70	75	80	85	90	95	100	105
To fit lower waist size (cm)	67	72	77	82	87	92	97	102	107	112
To fit hip size (cm)	87	92	97	102	107	112	117	122	127	132
In-leg length (cm)	78	80	80	82	82	84	84	86	86	86

BPL8092T

www.bisleyworkwear.com.au