

# COBRA

## SPECTACLE

ESSENTIAL WRAP-AROUND COMFORT



1663601 • Clear Lens



1663602 • Smoke Lens



1663610 • Twilight Lens






36 g

- + COMFORTABLE LIGHT WEIGHT FRAME**
- + TILT ADJUSTABLE TEMPLE ARMS, MAXIMISES INDIVIDUAL FIT.**
- + FULL EVA EYE SEAL TO MAXIMISE PROTECTION AGAINST DUST**
- + SUPER LOW PROFILE DESIGN**

**bollé**  
SAFETY

# COBRA SPECTACLE

## ESSENTIAL WRAP-AROUND COMFORT

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>COBRA SPECTACLE</b>	 Clear	1663601	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1663602	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Twilight	1663610	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

### LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

### OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
1. Range of luminous transmittance 43 -88% (twilight).
3. Range of luminous transmittance 8 -18% (smoke).

### APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Solar UV exposure
- Laboratory

### MAIN MARKETS

- Assembly and production work
- Emergency response
- Drilling
- Rigging
- Driving
- Solar UV exposure

### LENSES

- 2mm polycarbonate
- 9 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear, Smoke, and Twilight
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Twilight and Shade 5

### CLEANING AND STORAGE

**CLEANING :** Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	Non Applicable
STRAP	Non Applicable
FOAM	EVA Seal
SPARE LENSES	No

### FRAME MARKING

**AS/NZS 1337.1.2010 :** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

#### ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

#### NEW ZEALAND:

Bollé New Zealand Limited  
Unit 5, 114 Sawyers Arms Road  
Papanui, Christchurch 8052  
T: 03 3751400  
E: bolle@bolle.co.nz