

# Emergency Stainless Steel Combination Shower with Hand Operated No-Bowl Eyewash

Enware's emergency safety showers assist in the flushing of contaminants from the body with a deluge of flushing fluid and eye/face wash units help to flush contaminants and irritants from eyes and facial area.

Designed and manufactured in Australia. Stainless steel construction provides durability and reliability.

## FEATURES

- Independently tested for compliance to ANSI Z358.1 and AS4775
- Freestanding for stand-alone operation
- Stainless steel pipe work and stay-open ball valve
- Stainless steel 200mm (8") shower head assembly
- Stainless steel pull rod activated shower with high visibility yellow powder coating
- Push activated eyewash with soft aerated flow and integral auto-open dust covers
- Self-draining design reduces Legionella risk, particularly in tepid water applications
- Eye/face wash features "Vertech™ Technology" where dedicated eyewash and independently angled face wash streams deliver optimum coverage
- Zero velocity apex point provides more comfort and control for effective cleansing of eyes
- High visibility yellow powder coated push handle and foot pedal
- Balanced simultaneous operation

## ADDITIONAL OPTIONS

- Audio/Visual alarms for alerts
- Flow pressure & proximity switches to activate alarms and lights
- Thermal relief valve removes built-up hot water
- Signage compliant to AS1319
- Insulation of pipe work to moderate water temperature build up
- Anti-freeze valve for cold weather climates helps prevent water freezing
- NPT flange connectors
- Custom manufacturing & design

# ENBE060




## Product Codes

ENBE060	Standard Brushed Stainless Steel Finish
ENBE060GR	Green Powder Coated Finish
ENBE060OR	Orange Powder Coated Finish
ENBE060YE	Yellow Powder Coated Finish
ENBE060WH	White Powder Coated Finish

## Technical Information

Inlet Connection	25 mm (1") BSP
Water Supply Line Size	DN25 mm (1") Nominal Size
Minimum Performance Requirements	210 kPa Caution should be taken when pressure exceeds 550 kPa (80 psi)
Minimum Flow Requirements	Shower: 76 lpm (20 US gpm) Eyewash: 17 lpm (4.5 US gpm)
Waste Water Outlet Size	38 mm (1 1/2") OD
Mounting Base Plate Size	150 x 150 mm (5 9/10" x 5 9/10") with 4 Bolt Holes 11 mm (7/16")
Shipping Weight	approx. 10.6kg
Shipping Dimensions	1160 x 300 x 250 mm

Installation of emergency showers, eye and eye/face wash equipment shall be in accordance with AS/NZS4775-2007 or ANSI Standard Z358.1-2009 - whichever is applicable to the installation. Enware Australia advises:  
 1. Due to ongoing Research and Development, specifications may change without notice.  
 2. Component specifications may change on some export models.



Version: May 18

Call 1300 369 273  
[www.enware.com.au](http://www.enware.com.au)

Enware Australia Pty Limited  
 9 Endeavour Rd Caringbah NSW 2229 Australia  
 Ph: 02 8536 4000 info@enware.com.au



A range of spare parts are available to maintain equipment and replacement of damaged parts.

Description	Order Code
1 Eye and Eye/Face Wash Frame Only	ESPE002
2 Push Handle to suit Eye and Eye/Face Washes	ESPE010
3 Pull handle to activate shower	ESPE009
4 Shower arm and rose	ESPE005
9 Eye Wash Aerator and Washer	ESPE015
10 Eye wash outlet includes dustcovers & aerators (pair)	ESPE016

